



DVS Filtertechnik
Aan de Fremme 53
6269BK Margraten

www.dvs-filtertechnik.com
info@dvs-filtertechnik.com

Technical details CL65

Maximum Flow 65 m³/h
Gravity / Airlift / Pump feed
Pump Version has 30% less capacity
Water running height 12 cm

Material:

Housing PP 10/15 mm / Drum PP 15 mm
RVS 316/304 / Silicone sealant
Precise CNC machine cut PP-construction

Specifications:

Standard inputs and outputs acc. drawing
Changes to inputs and outputs possible after consultation
1 x 110 mm Waste Outlet
Diameter of drum 60 cm x 50 cm
Patented woven 75 micron steel mesh
2 x 90 mm Drum-Bypass
Removable spraybar
Removable waste water gutter
Installed Cleaningpomp 5 Bar
Space for 300 Liter Helix
1 Airdisc 35 cm
50 NM drive engin with 4 RPM
With cover

Control panel:

Automatic cleaning, plug and play with Sensor
Manual operation run/wash
Cleaning (turn/flushing) time adjustable
Cleaning level adjustable
3 plugs to have control over Drum filter motor , Cleaning and Pond-pump
Standard dry run protection for pond pump
All components built into modules wich quickly changeable
Comes with detailed instructions
CE approved

Warranty 2 years (not on the Sieve!)