

# DVS Filtertechniek Aan de Fremme 53 6269BK Margraten

# www.dvs-filtertechniek.com info@dvs-filtertechniek.com

### **Technical details ECO15**

Maximum Flow 15 m3/h Gravity / Airlift / Pump feed Pump Version has 30% less capacity Water running height 16 cm

#### Material:

Housing PP 10/15 mm / Drum PP 20/15 mm RVS 316/304 / Silicone sealant Precise CNC machine cut PP-construction

# **Specifications:**

Standard inputs and outputs acc. drawing
Changes to inputs and outputs possible after consultation
1 x 110 mm Waste Outlet
Diameter of drum 40 cm x 25 cm
Patented woven 75 micron steel mesh
2 x 90 mm Drum-Bypass
Removable spraybar
Removable waste water gutter
40 NM drive motor with 2,5 RPM
With cover

## **Control panel:**

Automatic cleaning, plug and play with stainles steel float switch
Manual operation run/wash
Cleaning (turn/flushing) time adjustable
Cleaning level adjustable
3 plugs to have control over Drum filter motor, Cleaning and Pond-pump
Standard dry run protection for pond pump
All components built into modules wich quickly changeable
Comes with detailed instructions
CE approved

Warranty 2 years (not on the Sieve!)