



**DVS Filtertechnik**  
**Aan de Fremme 53**  
**6269BK Margraten**

**[www.dvs-filtertechnik.com](http://www.dvs-filtertechnik.com)**  
**[info@dvs-filtertechnik.com](mailto:info@dvs-filtertechnik.com)**

#### **Technical details PP50**

Maximum Flow 50 m<sup>3</sup>/h  
Gravity / Airlift / Pump feed  
Pump Version has 30% less capacity  
Water running height 12 cm

#### **Material:**

Housing PP 10/15 mm / Drum PP 15 mm  
RVS 316/304 / Silicone sealant  
Precise CNC machine cut PP-construction

#### **Specifications:**

Standard inputs and outputs acc. drawing  
Changes to inputs and outputs possible after consultation  
1 x 110 mm Waste Outlet  
Diameter of drum 60 cm x 40 cm  
Patented woven 75 micron steel mesh  
2 x 90 mm Drum-Bypass  
Removable spraybar  
Removable waste water gutter  
50 NM drive motor with 4 RPM  
With cover

#### **Control panel:**

Automatic cleaning, plug and play with Sensor  
Manual operation run/wash  
Cleaning (turn/flushing) time adjustable  
Cleaning level adjustable  
3 plugs to have control over Drum filter motor, Cleaning and Pond-pump  
Standard dry run protection for pond pump  
All components built into modules which quickly changeable  
Comes with detailed instructions  
CE approved

Warranty 2 years (not on the Sieve!)