



### **Technical details PP65P**

Maximum Flow 65 m<sup>3</sup>/h  
Gravity / Airlift / Pump feed  
Pump Version has 30% less capacity  
Water running height 12 cm

### **Material:**

Housing PP 10/15 mm / Drum PP 15 mm  
RVS 316/304 / UV resistant Seal  
Precise CNC machine cut PP-construction

### **Specifications:**

Standard inputs and outputs acc. drawing  
Changes to inputs and outputs possible  
1 x 110 mm Waste Outlet  
Diameter of drum 60 cm x 50 cm  
Patented woven 75/120 micron stainless steel mesh  
2 x 90 mm Drum-Bypass  
Removable spraybar  
Removable waste water gutter / Waste cleaning optional  
Installed Cleaningpump 5 Bar  
50 NM drive engine with 4 RPM  
With Lid

### **Control panel:**

Automatic cleaning, plug and play with Sensor  
Manual operation run/wash  
Cleaning (turn/flushing) time adjustable  
Cleaning level adjustable  
3 plugs to have control over Drum filter motor, Cleaning and Pond-pump  
Standard dry run protection for pond pump  
All components built into modules which quickly changeable  
Comes with detailed instructions  
CE approved

Warranty 2 years (not on the Sieve!)